TMW 60 / 100 / 140 PAD-PRINTERS









TMW 60 / 100 / 140

The TMW pad printers are equipped with closed cup inkwells. This means that very low intervention will be needed to adjust or maintain the ink viscosity during operation. Its design with no side controls enables several machines to be placed side by side, making up groups for several colors or compact assemblies in automations.

The exclusive pneumatic cup release system grants a safe cup removal as well as precise doctoring pressure adjust. Optionally, the machine can be equipped with digital pressure gauges (line and doctoring), that enables a faster and more practical set up of the machine.

FEATURES		MODELS		
		TMW-60	TMW-100	TMW-140
Printing image size (max).		Ø 50mm	Ø 65mm	Ø 130mm
Cliché size		70x140 mm	85 x 185 mm	150x325mm
Cycles / hour (max.)		2400	3600	2000
Air consumption		7 SCFM	9 SCFM	15 SCFM
Dimension (mm)	Height	475	515	850
	Width	120	150	215
	Length	610	700	930
Machine weight		21 kg	23 kg	53 kg
Power		110/220V 20W	110/220V 20W	110/220V 20W



The acclaimed Dialog ® control panel is now equipped with a swift 16bit RISC processor. The unique system has didactically lit up keys that help the operator and make the equipment control handling extremely intuitive. Check all main features that make this control unbeatable:

- Auto diagnosis and cycle supervision: compressed air is disconnected automatically in case of obstruction of any movement, providing a safer environment to the operator (not available for TMW-60).
- Several types of pre-programmed cycle and operation cycles with parameters enabling the user to create and memorize his own cycle movement sequences.
- Five different timing parameters enable the adjustment of the cycle to some specific job.
- Memory for up to 50 adjustments for different products.
- Batch mode: it enables to plan the amount of pieces to be produced with alert sign at the end of the job.
- Three different kinds of counters: batch; user (it can be zeroed); machine lifespan (it cannot be zeroed).
- Production gauge: it reads production in parts per hour or minute, updated every cycle.
- Display selection: you choose what to appear on the display during operation with several options.
- Step by step mode: of great help at initial service adjustments.
- Extra outputs and inputs for automation and devices, many of them already programmed.
- Several other advantages: order a complete descriptive manual for more information.



WUTZL SISTEMAS DE IMPRESSÃO LTDA

Rua Silvestre Vasconcelos Calmon, 330 CEP 07020-001 - Guarulhos - SP - Brasil Fone: 55 11 6475-4233 - Fax: 55 11 6440-4524 www.wutzl.com.br e-mail: wutzl@wutzl.com.br